

# Product Data Sheet



## holzöl Weather-Oil Clear UV

Code	Description
7UV/00/30	<b>holzöl</b> Weather-Oil Clear UV
<b>Technical Data</b>	<b>holzöl</b> Weather-Oil Clear UV is a blend of oil, waxes and natural resins offering the best protection for exterior finishing.
<b>Properties</b>	<p><b>holzöl</b> Weather-Oil Clear UV prolongs the colour of the timber, preventing greying and oxidisation.</p> <p><b>holzöl</b> Weather-Oil Clear UV penetrates and nourishes the timber. Its microporous natural and UV inhibitors provide unrivalled weathering protection.</p> <p><b>Holzöl</b> Weather-Oil Clear UV can either be used alone as a coat on coat clear system or as protective topcoat for other <b>holzöl</b> exterior oils.</p>
<b>Mixing Guidelines</b>	Supplied ready for use (RFU). Stir well before use.
<b>Typical Handling</b>	<p>Drying Time: 10 - 12 hours, Recoat Time 10 - 12 hours</p> <p>These times are dependant amounts applied, the absorbency of the wooden substrate and application conditions.</p>
<b>Cleaning</b>	R047 - White Spirit should be used for cleaning equipment.
<b>Coverage</b>	Approximately 8-12m <sup>2</sup> per litre depending upon the application method, absorbency and surface quality of the timber being coated.
<b>System Guidelines</b>	<p>Morrells recommends the following guidance for use of this product:</p> <p>Before starting, make sure the surfaces of the timber to be coated should be clean, dry and free from oils, greases, waxes, silicones, old finishes etc.</p> <p><b>Typical Clear Finish:</b></p> <ul style="list-style-type: none"> <li>○ Apply a coat of <b>holzöl</b> Weather-Oil Clear, by brush, or roller.</li> <li>○ Allow 10 - 12 hours to dry, then lightly abrade with 220/240 silicon carbide abrasive.</li> <li>○ Apply a second coat of <b>holzöl</b> Weather-Oil Clear, as above.</li> </ul> <p><b>Typical Stain Finish:</b></p> <ul style="list-style-type: none"> <li>○ Apply a coat of <b>holzöl</b> Weather-Stain Oil, by brush or roller. Apply the oil in the direction of the wood grain.</li> <li>○ Allow 10 - 12 hours to dry, then lightly abrade with 220/240 silicon carbide abrasive.</li> </ul>



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN  
Tel: 08705 60 61 62 Fax: 08705 604 604 Email: enquiries@morrells.co.uk Web: www.morrells.co.uk

Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT. Reg No GB 712 5048 66



	<ul style="list-style-type: none"> <li>○ Apply a <b>holzöl</b> Weather-Oil Clear, as above.</li> </ul> <p>Using this product in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.</p>
<b>Maintenance</b>	<p>The <b>holzöl</b> Weather-Oil Clear UV should be maintained using a clean, lightly dampened cloth.</p> <p>If the finish becomes "tired" looking or damaged, abrade with 240/320 silicon carbide abrasive and apply a further coat of <b>holzöl</b> Weather-Oil Clear UV.</p>
<b>Important Information</b>	<ul style="list-style-type: none"> <li>➤ Designed for manual (brush or roller) application.</li> <li>➤ Always test the product on a spare surface or inconspicuous area to assess compatibility, colour and finish.</li> <li>➤ Sawdust, cloths, brushes, papers and similar products containing wet product may cause spontaneous combustion. Either allow to fully dry or drench in water before disposal.</li> <li>➤ Product should be stored above 5°C and protected from frost.</li> <li>➤ Optimum application is achieved between 20°C and 25°C with good air movement and ventilation.</li> <li>➤ Meets the VOC requirements of 2004/42/EC, Annex II(cat A/i).</li> </ul>
<b>Health &amp; Safety</b>	<p>Reference should be made to the appropriate MSDS for this product, which can be found at <a href="http://www.morrells.co.uk">www.morrells.co.uk</a></p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p>

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN  
Tel: 08705 60 61 62 Fax: 08705 604 604 Email: [enquiries@morrells.co.uk](mailto:enquiries@morrells.co.uk) Web: [www.morrells.co.uk](http://www.morrells.co.uk)

Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT. Reg No GB 712 5048 66

